

## Overview

The Albutt Shear King Mini high capacity shear grab is designed to be used with telehandlers and wheeled loaders with a minimum lift of 3-4 tonnes.

The grabs have a capacity of 1.40m<sup>3</sup>, 1.60m<sup>3</sup> and 1.80m<sup>3</sup> and a width of 1.90m, 2.20m and 2.50m.

Users wanting to handle large amounts of silage and maximise their machines' productivity are the ideal customers for this new grab.

With a large capacity, the number of cuts and journey times can be reduced, improving silage quality and handling efficiency.

## Features

- Hardox tines welded into heavy duty box section; 13, 15 or 17
- Hardox cutting blades to the front and side of the grab
- Twin double acting hydraulic rams; 110mm bore
- Heavy duty box sections; 10mm wall
- Grab pivots 60mm and bushed, ram pivots 40mm and bushed
- Front grab double skinned for maximum strength
- Long term reliability with a great cut for a clean clamp face
- Suitable for grass, maize and wholecrop

## Models

Model	Tines	Width	Weight	m <sup>3</sup>
SKM190HX	13	1.90m	1010kgs	1.40m <sup>3</sup>
SKM220HX	15	2.20m	1120kgs	1.60m <sup>3</sup>
SKM250HX	17	2.50m	1220kgs	1.80m <sup>3</sup>



Albutt Ltd | UK | GL20 7AR  
Tel. 01242620252

Robin Normington. 07778942138 | robin@albutt.co.uk

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

