

Overview

The Albutt LG series of timber grapples are designed to be used with telehandler, loader or tractor 3 point linkage. The attachments have a lift capacity of 2.5 & 4.0 tonnes. The grapple has a rotate function allowing timber to be positioned when loading timber trucks. Grapple arms are manufactured from Domex high tensile steel for high strength and long term reliability. Two hydraulic services or a change over valve are required to operate both grapple and rotator. The 360 degree rotator allows for accurate positioning of timber.

Features

- Curved grapple arms allow timber to roll into the grapple arms
- 360 degree rotator
- Hydraulic ram protected
- Timber Grapple manufactured from high tensile Hardox steel
- All grease points easily accessed with grapple closed
- Handles timber 50mm to 700mm diameter
- Serrated blade help steady load
- Telehandler, Tractor Loader or Wheeled Loader brackets included
- Brackets bolted on; can be easily changed if machine brand is changed in future

Models

Model	Lift Capacity	Jaw Opening	Weight
LG700	2500kgs	1450mm	295kgs
LG800	4000kgs	1890mm	330kgs



Albutt Ltd | UK | GL20 7AR
Tel. 01242620252

Robin Normington. 07778942138 | robin@albutt.co.uk

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

