

Overview

The Albutt LG series of timber grapples are designed to be used with telehandler, loader or tractor 3 point linkage. The attachments have a lift capacity of 2.5 & 4.0 tonnes. The grapple has a rotate function allowing timber to be positioned when loading timber trucks. Grapple arms are manufactured from Strenx high tensile steel for high strength and long term reliability. Two hydraulic services or a change over valve are required to operate both grapple and rotator. The 360 degree rotator allows for accurate positioning of timber.

Features

- Curved grapple arms allow timber to roll into the grapple arms
- 360 degree rotator
- Hydraulic ram protected
- Timber Grapple manufactured from high tensile Hardox steel
- All grease points easily accessed with grapple closed
- Handles timber 50mm to 700mm diameter
- Serrated blade help steady load
- Telehandler, Tractor Loader or Wheeled Loader brackets included
- Brackets bolted on; can be easily changed if machine brand is changed in future

Models

| Model | Lift Capacity | Jaw Opening | Weight |
|-------|---------------|-------------|--------|
| LG700 | 2500kgs | 1450mm | 295kgs |
| LG800 | 4000kgs | 1890mm | 330kgs |



Albutt Ltd | UK | GL20 7AR
 Tel. 01242620252
 Dan Cross. 07720087264 | dan@albutt.co.uk
 www.albutt.co.uk

