

Overview

The Albutt Shear Bucket range is based on the ultra high strength design of the Shear King range, providing excellent cutting capabilities on all silage types. The grab is taken directly off of the Shear King and features the same high tensile steels (Hardox & Strenx) throughout. The bucket floor is braced by underside Hardox tines for maximum durability. Across the front edge of the bucket is a specially commissioned Hardox cutting edge, sharpened to enter the pit face as clean as possible. This process is bolstered by cutting edges to the side profiles of the bucket.

Features

- Hardox cutting blades to the front and side of the grab
- High tensile STRENX front blade
- Hardox cutting edge across front of bucket floor
- Twin double acting hydraulic rams; 110mm bore
- Heavy duty box sections; 10mm wall
- Grab pivots 60mm ram pivots 40mm
- Front grab double skinned for maximum strength
- Long term reliability with a great, clean cut
- Suitable for maize, wholecrop or precision chopped grass silage
- Hardox Tines brace the bucket floor
- Suitable for machines with a 4 tonne plus lift capacity

Models

Model	Capacity	Width	Weight
SKB220HX	2.20m ³	2200mm	1520kg
SKB250HX	2.50m ³	2500mm	1590kg



Albutt Ltd | UK | GL20 7AR
Tel. 01242620252
Dan Cross. 07720087264 | dan@albutt.co.uk
www.albutt.co.uk

