

## Overview

The Albutt range of Heavy Duty Buck Rakes are designed for use with high horsepower tractors or loading shovels.

Tractor horsepower requirement is 160hp rear linkage and 180hp front linkage. Front linkage rating requirement is 5 tonnes.

The range is renowned for being the global market leader with many repeat orders from Australia, New Zealand, USA and Canada. An unrivalled specification includes a 200 x 100mm tine holder, high grade mesh gate and high capacity hydraulic cylinders.

## Features

- 1650mm genuine Hardox base tines
- Double side tines
- 200 x 100mm tine holder
- High flow divider valve to prevent gate twists on uneven loads
- 75mm ram bore size
- 35mm diameter ram pivot pins
- 5 hole top link positions
- Angled tine holder top to prevent silage build up
- Leant forward spill frame on gate
- High grade mesh gate gives strength but great visibility
- Double profile gate mounting prevents arms bending
- 60mm diameter main pivot pin

## Models

Model	Width	Tines	Capacity	Weight
B808PPHX	8'	10	4.80m3	1250kgs
B809PPHX	9'	11	5.43m3	1320kgs
B810PPHX	10'	12	6.09m3	1400kgs
B812PPHX	12'	14	7.39m3	1570kgs

**HARDOX**<sup>®</sup>  
WEAR PLATE



Albutt Ltd | UK | GL20 7AR

Tel. 01242620252

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

