

## Overview

The Albutt Shear Bucket range is based on the ultra high strength design of our Hardox Shear Grab range, providing excellent cutting capabilities on all silage types. The grab is taken directly off of the Hardox Shear Grab and is enhanced with the feature a STRENX high tensile steel front. The bucket floor is braced by underside HARDOX tines for maximum durability. Across the front edge of the bucket is a specially commissioned HARDOX cutting edge, sharpened to enter the pit face as clean as possible. This process is bolstered by cutting edges to the side profiles of the bucket.

## Features

- Hardox cutting blades to the front and side of the grab
- High tensile STRENX front blade
- Hardox cutting edge across front of bucket floor
- Twin double acting hydraulic rams; 110mm bore
- Heavy duty box sections; 8mm wall
- Grab pivots 50mm
- Front grab double skinned for maximum strength
- Long term reliability with a great, clean cut
- Suitable for maize, wholecrop or precision chopped grass silage
- Hardox tines brace the bucket floor
- Suitable for machines with a 2-3 tonne lift capacity

## Models

Model	Capacity	Width	Weight
SB190HX	1.00m3	1900mm	760kg
SB220HX	1.15m3	2200mm	815kg



Albutt Ltd | UK | GL20 7AR

Tel. 01242620252

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

