



XL RANGE HIGH TIP BUCKETS

Overview

The Albutt XL range of High Tip Buckets are designed for high capacity shovels operating in intense cycle environments. Launching from a Hardox cradle, the high capacity, Domex shelled, bucket provides increased height and forward reach – improving both cycle times and productivity of its prime mover. Hardox wear pads are used throughout – both adding to the strength of the bucket and increasing its service life. Maintenance is also made easy with the remote greasing facility – no need to stretch into those hard to reach places to grease the attachment. Suitable for loading shovels with a 6.50 to 7.50 tonne lift capacity, the XL High Tip Bucket Range is available in 4.76m³, 4.98m³ and 5.26m³ capacities.

Features

- Fitted with long life cutting edge 500 Brinell hardened boron steel
- Extra 300 x 30mm 500 Brinell Bolt on Toe Plate as standard
- Cradle manufactured from Hardox 500
- Twin hydraulic rams
- Bucket cushioning – heavy duty rubber bump stops
- Remote greasing points
- Hardox wear pads
- Domex Shell
- Over centre valve

Models

Model	Capacity	Width	Weight
A186-100HTBL	5.26m ³	10'	2990 kg
A176-96HTBL	4.98m ³	9'6"	2840 kg
A166-90HTBL	4.76m ³	9'	2691 kg



Albutt Ltd | UK | GL20 7AR
Tel. 01242620252

Robin Normington. 07778942138 | robin@albutt.co.uk

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

