

## Overview

The Albutt Shear King Mini high capacity shear grab is designed to be used with telehandlers and wheeled loaders with a minimum lift of 3-4 tonnes.

The grabs have a capacity of 1.40m<sup>3</sup>, 1.60m<sup>3</sup> and 1.80m<sup>3</sup> and a width of 1.90m, 2.20m and 2.50m.

Users who handle large amounts of silage and maximise their machines' productivity are the ideal customers for this new grab. With a large capacity, the number of cuts and journey times can be reduced, improving silage quality and handling efficiency.

## Features

- Hardox tines welded into heavy duty box section; 13, 15 or 17
- Hardox cutting blades to the front and side of the grab
- Twin double acting hydraulic rams; 110mm bore
- Heavy duty box sections; 10mm wall
- Grab pivots 60mm and bushed, ram pivots 40mm and bushed
- Front grab double skinned for maximum strength
- Long term reliability with a great cut for a clean clamp face
- Suitable for grass, maize and wholecrop
- STRENX high tensile steel grab
- Wide opening – 946mm

## Models

Model	Width	Capacity	Weight
SKM190HX	1900mm	1.40m <sup>3</sup>	1010kg
SKM220HX	2200mm	1.60m <sup>3</sup>	1120kg
SKM250HX	2500mm	1.80m <sup>3</sup>	1220kg



Albutt Ltd | UK | GL20 7AR

Tel. 01242620252

Dan Cross. 07720087264 | dan@albutt.co.uk

www.albutt.co.uk

